

Technical data sheet

Interception rod holder for ridge tiles

Item number: 5403330



Rod holder for ridge tiles, for simple, quick and safe fastening of Ø 16 mm interception rods

- System consisting of holder made of V2A stainless steel and aluminium interception rod
- Quick and easy mounting thanks to pre-mounted air-termination rod
- Air-termination rod length:
- Air-termination rod length: 1,000 mm
- Width adjustable between 180–260 mm
- Spacing of the ridge holders: 110 mm (5403330)
- Spacing of the ridge holders: 300 mm (5403333)

Application: To protect roof structures such as photovoltaic and TV/SAT systems.

A2 Stainless steel

Master data

Item number	5403330
Type	F-FIX-132
Description 1	Interception rod holder
Description 2	for ridge tiles
Manufacturer	OBO
Dimension	1m
Material	Stainless steel, rustproof 1.4301
Smallest sales unit	1
Unit of quantity	Units
Weight	62 kg
Weight unit	kg/100 pairs
CO2 Footprint (GWP) Cradle-to-Gate	2,9772 kg CO2e / 1 Piece


Technical data sheet

Interception rod holder for ridge tiles

Item number: 5403330



Dimensions



Length	110 mm
Height	1 000 mm
Dimension L	110 mm

Technical specifications

ROHS-conformant	yes
Clamping range D, max.	260 mm
Clamping range D, min.	180 mm